

OWNER'S MANUAL

3-Sided Electric Fireplace



AC 220V-240V 50Hz 1600-1800W

MODEL

☐ EF-NORF42

☐ EF-NORF50

☐ EF-NORF60

☐ EF-NORF72

CAUTION

Read and understand this entire owner's manual, including all safety information, **BEFORE** plugging in or using this product. Failure to do so could result in fire, electric shock, or serious personal injury.

Keep this owner's manual for future reference. If you sell or give this product away, make sure this manual accompanies this product.

IMPORTANT SAFETY INFORMATION!

CAUTION

This heater is hot when in use.

Read all instructions before installing or using this heater.

To avoid burns, **DO NOT** let bare skin touch hot surfaces. If provided, use handles when moving this heater. Keep combustible materials, such as furniture, pillows, bedding, papers, clothes, and curtains at least 3 feet (1.0 m) from the front of the heater and keep them away from the sides and rear.

Extreme caution is necessary when any heater is used by or near children or invalids and whenever the heater is left operating and unattended.

DO NOT operate any heater with a damaged cord or plug or after the heater malfunctions, has been dropped or damaged in any manner.

Return to authorized service facility for examination and/or repair.

Indoor use **ONLY**, **DO NOT** use out doors.

This heater is not intended for use in bathrooms, laundry areas and similar indoor locations.

NEVER locate heater where it may fall into a bathtub or other water container.

DO NOT run cord under carpeting.

DO NOT cover cord with throw rugs, runners, or similar coverings. Arrange cord away from traffic area and where it will not be tipped over.

To disconnect heater, turn controls to off, then remove plug from outlet.

DO NOT insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the heater.

To prevent a possible fire, do not block air intakes or exhaust in any manner. **DO NOT** use on soft surfaces, like a bed, where openings may become blocked.

A heater has hot and arcing or sparking parts inside. **DO NOT** use it in areas where gasoline, or flammable liquids are used or stored.

Use this heater only as describes in this manual. Any other use not recommended by the manufacturer may cause fire, electric shock, or injury to persons.

DANGER-HIGH Temperatures may be generated under certain abnormal conditions. **DO NOT** partially or fully cover or obstruct the front of this heater.

Replacement of the lamps should be done only while the heater is disconnected from the supply circuit.

This appliance is not intended for use by persons (including children) with reduced physical, sensory or capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

Children should be supervised to ensure that they do not play with the appliance.

CAUTION

AVOID FIRE ! Regularly inspect all air vents to make sure they are free from dust, lint, or other blockage. Unplug the unit and clean with a vacuum **ONLY**. **DO NOT** rinse or get wet.

CAUTION

In order to avoid a hazard due to inadvertent resetting of the thermal cut-out, this appliance must not be supplied through an external switching device, such as a timer, or connected to a circuit that is regularly switched on and off by the utility.

SAVE THESE INSTRUCTIONS!

PREPARATION

CAUTION











This product includes a **GLASS** panel! Always use extreme caution when handling glass. Failure to do so could result in personal injury or property damage.

Remove all parts and hardware from the carton and place them on a clean, soft, dry surface. Parts and assembly steps are grouped for wall-hanging use. Check the parts list to make sure nothing is missing. Dispose of packaging materials properly. Please recycle whenever possible.


You will need the following tools (not included):

- a. Phillips screwdriver
- b. stud finder
- c. level
- d. tape measure
- e. electric drill
- f. 1/4" wood drill bit
- g. hammer

PARTS & HARDWARE

 A Electric fireplace	 B Screws	 C Drywall anchors
 D Remote Control	 E Logs	 F Smoky Crystals
 G Feet	 H Metal L-Bracket	 Z Screws
 I Mounting Bracket (Pre-fixed to the fireplace back)		

SPECIFICATION & DIMENSION



MODEL	A	B	C	D	E	F	G	H	I
EF-NORF42	42" 1067mm	16.14" 410mm	7.35" 186.6mm	13.78" 350mm	41.93" 1065mm	9.6" 243.8mm	13.78" 350mm	2.36" 60mm	11.42" 290mm
EF-NORF50	50" 1270mm	16.14" 410mm	7.35" 186.6mm	13.78" 350mm	49.92" 1268mm	9.6" 243.8mm	13.78" 350mm	2.36" 60mm	11.42" 290mm
EF-NORF60	60" 1524mm	16.14" 410mm	7.35" 186.6mm	13.78" 350mm	59.92" 1522mm	9.6" 243.8mm	13.78" 350mm	2.36" 60mm	11.42" 290mm
EF-NORF72	72" 1828mm	16.14" 410mm	7.35" 186.6mm	13.78" 350mm	71.89" 1826mm	9.6" 243.8mm	13.78" 350mm	2.36" 60mm	11.42" 290mm

INSTALLATION & ASSEMBLY

Installation

Your appliance is designed to be recessed or wall mounted. Select a suitable location that is not susceptible to moisture and is away from drapes, furniture, and high traffic areas.

NOTICE

Follow all national and local electrical codes.

⚠ CAUTION

When using paints or varnishes to finish the mantel, make sure they are heat resistant to prevent discoloration.


⚠ CAUTION

ALWAYS unplug this fireplace before assembly or cleaning, or before relocating. Failure to do so could result in electric shock, fire, or personal injury.

MINIMUM CLEARANCE TO COMBUSTIBLES

MEASUREMENTS ARE TAKEN FROM THE GLASS FRONT


BOTTOM	0 mm (0")	TOP	300 mm (11.8") to mantel
SIDES	0 mm (0")	FRONT	914 mm (36")
BACK	0 mm (0")		




INSTALLATION & ASSEMBLY

Front Glass Installation / Removal

STEP 1: Remove the glass box from the back of the fireplace. Cut the box, and take out the front glass.



STEP 2: Have two people lift the glass panel. Place the glass into the design slot position.



STEP 3: Fix with the screws (**Z**) to the top of the glass panel.

STEP 4: Reverse these steps to remove the front glass.


INSTALLATION & ASSEMBLY

Wall Recessed Installation

Your appliance facilitates three different installation configurations: **three-sided**, **two-sided**, and **single-sided**.


THREE-SIDED INSTALLATION

Glass exposed on **front, left, AND right** sides.
Appliance is fully recessed into the wall with both sides open.




TWO-SIDED INSTALLATION

Glass exposed on **front AND left OR right** side.
Appliance is fully recessed into the wall with one side open.




SINGLE-SIDED INSTALLATION

Glass exposed on **front ONLY**.
Appliance is fully recessed into the wall.



INSTALLATION & ASSEMBLY

Installation / Rough Framing



NOTICE

Make an opening for the fireplace according to requested measurement.

MODEL	W	D	H
EF-NORF42	42.08" 1069mm	7.72" 196mm	14.17" 360mm
EF-NORF50	50.08" 1272mm	7.72" 196mm	14.17" 360mm
EF-NORF60	60.08" 1526mm	7.72" 196mm	14.17" 360mm
EF-NORF72	72.05" 1830mm	7.72" 196mm	14.17" 360mm

INSTALLATION & ASSEMBLY

Installation / Rough Framing

NOTICE

Appliance is NOT load-bearing. Carefully consider weight of finishing materials when constructing rough framing.


Ensure installation complies with all local building codes and requirements.

All viewing options (single-sided, two-sided [left or right], and three-sided) use the same framing dimensions.


NOTICE

When installed fully recessed into the wall, please fix the fireplace with supplied short wood screws (B) under the ember bed. See below illustration.

STEP 1: Place the appliance into the wall, refer to Figure 1 and Figure 2.



STEP 2: Remove the left and right side plastic strip brackets, refer to Figure 3.



STEP 3: Secure the appliance with screws as shown in the picture, refer to Figure 4.

INSTALLATION & ASSEMBLY

Wall Mounted Installation


Due to the many different materials used on different walls, it is highly recommended that you consult your local builder before you install this appliance on the wall.

You need two people to install the fireplace on a wall.

STEP 1: Select a location that is not prone to moisture and is located at least 36" (914mm) away from combustible materials such as curtains, drapes, furniture, bedding, paper, etc.

STEP 2: Have two people hold the appliance against the wall to determine the final location.

STEP 3: Place unit face down on a soft, nonabrasive surface. Remove the bracket from the back of the unit by removing the screws.



STEP 4: Mark out location, then mount the bracket(s) onto the wall using the supplied screws. This bracket **MUST** have the hooks facing upward and be level.

NOTICE

It is strongly recommended that the mounting bracket (I) be screwed into the wall studs where possible. If the wall studs cannot be used, ensure that the supplied plastic anchors are used to affix the bracket to the wall and the bracket is adequately secured.

STEP 5: With the wall mounting bracket installed have two people lift the appliance up and insert the two hooks on the bracket into the two slots on the back of the appliance.

STEP 6: Check the appliance for stability ensuring that the bracket will not pull free from the wall.





Illustration of wall bracket for model EF-NORF72


INSTALLATION & ASSEMBLY

“L” Shape Metal Bracket Installation


STEP 1: Remove the silver screw at the bottom of the appliance. Set the screw aside, refer to Figure 6.



STEP 2: Using the screw removed in step 1, attach the metal L-bracket (H) to the bottom of the fireplace box, refer to Figure 7.



STEP 3: Install the plastic wall anchor (C) into the drywall. Install the longer screw (B) into the hole of the L-bracket and then into the wall anchor to secure the fireplace from coming off the wall, refer to Figure 8.




INSTALLATION & ASSEMBLY

Feet Bracket Installation


STEP 1: Remove all the screws at the bottom of the appliance. Set the screws aside, refer to Figure 9.

9



STEP 2: Using the screws previously removed, attached the two feet (supplied) to the bottom of the fireplace box, refer to Figure 10.

10



INSTALLATION & ASSEMBLY

Crystals and Logs Installation

NOTICE

Please install the ember bed media to your preference.

STEP 1: The glass front must be removed and the appliance must be mounted in its final location before the ember bed media can be installed.

11



STEP 2: Carefully place the smoky crystals (F) into the bottom tray on the front of the appliance as shown. Apply an even layer from side to side, refer to Figure 11.

12



STEP 3: Carefully place the logs (E) onto the crystals, refer to Figure 12.

STEP 4: Re-install the front glass.

OPERATION

CAUTION

Read and understand this entire owner's manual, including all safety information, before plugging in or using this product. Failure to do so could result in electric shock, fire, serious injury, or death.

Power

Plug the power cord into a **220-240 Volt 15 Amp** grounded outlet (see **IMPORTANT SAFETY INFORMATION** on Page 2). Make sure the outlet is in good condition and that the plug is not loose. **NEVER** exceed the maximum maximum amperage for the circuit. **DO NOT** plug other appliances into the same circuit.

NOTICE



When the heater is first turned on, a slight odor may be present. This is normal and should not occur again unless the heater is not used for a long period of time.

To improve operation, aim the remote control at the front of the fireplace. **DO NOT** press the buttons too quickly. Give the unit time to respond to each command.











Methods of Operation

This electric fireplace can be operated by the **TOUCH PANEL**, by the battery-powered **REMOTE CONTROL**, or by the **TUYA APP**.


Before operating, please review the **IMPORTANT SAFETY INFORMATION** on Page 2, and heed all warnings.



REMOTE CONTROL / TOUCH PANEL: FUNCTIONS

BUTTON	FUNCTION	ACTION & INDICATION																																						
	ON: Enables control panel functions and remote control. Turns on flame effect. OFF: Disables control panel functions and remote control. Turns off flame effect.	1. Press once. Indicator light turns on. Power turns on. All functions enabled. 2. Press again. Flame effect turns off. Unit goes to standby. All functions turn off.																																						
	COLOR button: Makes the color flame effect changing. NOTE: color effect stays on until power button is turned off. Color flame effect must be on for heater to turn on.	1. Press once. Flame color effect gets changing. 2. Press again. until desired setting is reached. In total with 15 color flames.																																						
	HEATER button: Turns heater on and off. NOTE: The heater only works when the flame effect is on. If the flame effect is off, the heater will not turn on. NOTE: Heater button can be locked or unlocked by holding the Heater button for 5 seconds.	1. Press once. Indicator lights up. Fan blows cool air for 20 seconds. 900W heater turns on and blows warm air. 2. Press again. Indicator lights up. 1800W heater turns on and blows hot air. 3. Press again. Heaters turn off. The fan blows cool air for 30 seconds to allow heater to cool down, then turns off.																																						
	TEMPERATURE button: Changes the temperature settings. 1. Press once. Touch panel indicator becomes active. 2. Press again. until desired setting is reached. The display shows below settings	<table><tr><th>Display Value</th><th>NO</th><th>1</th><th>2</th><th>3</th><th>4</th><th>5</th><th>6</th><th>7</th><th>8</th><th>9</th><th>10</th><th>11</th></tr><tr><td rowspan="2">Temperature</td><td>°C</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td><td>27</td><td>28</td><td>29</td><td>30</td></tr><tr><td>°F</td><td>68</td><td>70</td><td>72</td><td>74</td><td>76</td><td>78</td><td>80</td><td>82</td><td>84</td><td>86</td><td>88</td></tr></table> NOTE: Press the button for 5 seconds to switch between °C and °F.	Display Value	NO	1	2	3	4	5	6	7	8	9	10	11	Temperature	°C	20	21	22	23	24	25	26	27	28	29	30	°F	68	70	72	74	76	78	80	82	84	86	88
Display Value	NO	1	2	3	4	5	6	7	8	9	10	11																												
Temperature	°C	20	21	22	23	24	25	26	27	28	29	30																												
	°F	68	70	72	74	76	78	80	82	84	86	88																												
	TIMER button: Controls timer settings to turn off fireplace at selected time. Settings range from 0.5 hour to 8 hours.	1. Press once. Indicator light turns on. Timer defaults to 0.5 hour. 2. Press again. until desired setting is reached. Indicator lights show setting.																																						
	FLAME SPEED button: Controls the speed of the flame. There are 3 flame speed settings: 01 (slow), 02 (medium), 03 (fast).	1. Press once. Flame speed gets changing. 2. Press again. until desired setting is reached. Display shows the setting. The Default setting is 02 (medium speed)																																						
	FLAME BRIGHTNESS button: Makes flame dimmer and brighter.	1. Press once. Flame brightness is enabled. 2. Press again. until desired setting is reached.																																						
	EMBER BED LIGHTS button: Turns on media bed and changes color. NOTE: This fireplace has memory function for ember bed lighting.	1. Press once. Ember bed turns on. 2. Press again. until desired setting is reached. There is a total of 15 ember bed colors.																																						
	EMBER BED BRIGHTNESS button: Makes media bed dimmer and brighter.	1. Press once. Brightness becomes active. 2. Press again. until desired setting is reached. There is a total of 4 brightness levels and 1 pulsating level.																																						
	DOWN LIGHT button: Turns on the LED down light and changes color. NOTE: This fireplace has memory function for the down light.	1. Press once. LED down light is powered on. 2. Press again. until desired setting is reached. There is a total of 15 down light colors.																																						

REMOTE CONTROL / TOUCH PANEL: FUNCTIONS

BUTTON	FUNCTION	ACTION & INDICATION
	CRACKING SOUND button: Makes cracking sound low or high.	<ol style="list-style-type: none">1. Press once. Cracking sound is enabled.2. Press again. until desired setting is reached.

TEMPERATURE LIMITING CONTROL

NOTICE

This heater is equipped with a Temperature Limiting Control. Should the heater reach an unsafe temperature, the heater will automatically turn OFF.

TO RESET

1. Turn the ON/OFF switch on the CONTROL PANEL to OFF. Wait 5 minutes.
2. Unplug the power cord from the outlet.
3. Inspect the fireplace to make sure no vents are blocked or clogged with dust or lint. If they are, use a vacuum to clean the vent areas.
4. With the POWER switch in the OFF position, plug the power cord back into the outlet.
5. If the problem continues, have your outlet and wiring inspected by a professional.

REMOTE CONTROL BATTERY INFORMATION

The remote control uses two AAA batteries (not included).

CAUTION

NEVER dispose of batteries in fire.

Failure to observe this precaution may result in an explosion. Dispose of batteries at your local hazardous material processing center.

CARE & MAINTENANCE

Cleaning

CAUTION

ALWAYS turn the heater **OFF** and unplug the power cord from the outlet before cleaning, performing maintenance, or moving this fireplace. Failure to do so could result in **electric shock, fire, or personal injury**.

NEVER immerse in water or spray with water. Doing so could result in **electric shock, fire, or personal injury**.

Metal:

Buff using a soft cloth, slightly dampened with a citrus oil-based product.

DO NOT use brass polish or household cleaners as these products will damage the metal trim.

Glass:

Use a good quality glass cleaner sprayed onto a cloth or towel. Dry thoroughly with a paper towel or lint-free cloth.

NEVER use abrasive cleansers, liquid sprays, or any cleaner that could scratch the surface.

Vents:

Use a vacuum or duster to remove dust and dirt from the heater and vent areas.

Plastic:

Wipe gently with a slightly damp cloth and a mild solution of dish soap and warm water.

NEVER use abrasive cleansers, liquid sprays, or any cleaner that could scratch the surface.

Maintenance

CAUTION

Risk of electric shock! DO NOT OPEN any panels ! No user-serviceable parts inside!

ALWAYS turn the heater **OFF** and unplug the power cord from the outlet before cleaning, performing maintenance, or moving this fireplace. Failure to do so could result in electric shock, fire, or personal injury.

Electrical and Moving Parts:

The fan motors are lubricated at the factory and will not require lubrication.

Electrical components are integrated in the fireplace and are not serviceable by the consumer.

Storage:

Store heater in a clean dry place when not in use.

CAUTION

NO SERVICING of the internal or electrical parts should be performed by the consumer. Do not service the unit yourself.